moon glo

DATASHEET

MoonGlo[™] Machine/Vehicle Package



MoonGlo balloon lighting on any compatible mount adds 360 degrees of glare-free light to mobile utility vehicles or heavy equipment in minutes.

| STANDARD MACHINE/VEHICLE PACKAGE (WITHOUT MOUNT) | | | |
|--|--|--|--|
| Item | Specifications | | |
| Balloon Light | See back page of datasheet for options | | |
| 4-stage Telescoping Pole | 48" (4') collapsed, 158" (13'2") extended, chromed steel | | |
| Canvas Light Storage Bag | 11" diameter x 58" long, collapsible | | |

| ACCESSORIES (OPTIONAL) | | | |
|--------------------------|--|--|--|
| Item | Specifications | | |
| Machine Mount | 2" x 2" wide x 9.25" tall | | |
| Spring Mount | 3" x 3" wide x 18.5" tall, 3" diameter spring | | |
| Hitch Mount | 2" or 1-1/4" receiver size, 10"–24" tailgate clearance length (custom clearance lengths available upon request) | | |
| Rigid Light Storage Tube | 11" diameter x 56" long | | |

COMMON USES

Asphalt and concrete paving machines, rollers, utility trucks, emergency response vehicles, etc.

RECOMMENDATION

Use a Spring Mount adapter on any piece of equipment that will be working around cables, trees, curbs, etc. Basically, if your operator likes to drive like they're in a tank, get one.






MOONGLO™ MACHINE/VEHICLE PACKAGE


Balloon Light Options


MoonGlo builds a Balloon Light structure with the choice of Metal Halide or LED light source.

| BALLOON LIGHT MODELS [†] | | | | | | |
|---|--|------------------------------------|------------------|------------------|--|--|
| Lamp Option | Specifications (each) | Light Performance* (1 or 2 lights) | | | | |
| (1) 1000 watt Metal Halide (Model BT-37) | 115,000 Lumens, 3700K. Remote Ballast Power: 120 volt, 8.6 amps. 10-15 minute warm up period. | @ 12' Center of Light | | | | |
| | | Radius | Foot Candles (1) | Foot Candles (2) | | |
| | | At Base | — | — | | |
| | | 10′ | 41 | 73 | | |
| | | 20′ | 11 | 20 | | |
| | | 30′ | 6 | 7.75 | | |
| | | 40′ | 3 | 4.25 | | |
| | | 50′ | 1.72 | 2.86 | | |
| | | 60′ | 1.14 | 1.79 | | |
| (1) 300 watt LED | 36,000 Lumens. 25' power cord. 120volt, 3 amps. Instant on. | @ 12' Center of Light | | | | |
| | | Radius | Foot Candles (1) | Foot Candles (2) | | |
| | | At Base | 49.7 | 69 | | |
| | | 10′ | 17.8 | 27 | | |
| | | 20′ | 5.6 | 10 | | |
| | | 30′ | 2.1 | 4.5 | | |
| | | 40′ | 1.15 | 2.5 | | |
| | | 50′ | 0.71 | 1.5 | | |
| | | 60′ | 0.45 | 1 | | |

[†] ADDITIONAL LIGHT OUTPUT CHARTS ARE AVAILABLE FOR DIFFERENT HEIGHTS AND FURTHER DISTANCES UPON REQUEST. ^{*} ALL METER READINGS IN FOOT CANDLES ARE TAKEN FROM WAIST HEIGHT WITH NO OTHER LIGHT PRESENT.







COMPATIBILITY

MoonGlo balloon lights are interchangeable with all of our mounting systems. The same MoonGlo Balloon Light used on your paving machine can also be used on a MoonGlo Tripod system or used on a portable light tower equipped with a MoonGlo Balloon Light Tower Conversion. Being able to quickly adapt to the unexpected requires versatility — *every* work zone benefits from versatility.

PARTS & SERVICE

All MoonGlo parts are readily available and in stock. MoonGlo is always available to discuss your lighting needs. We have many years of experience with work zone/site equipment and event lighting.



DATASHEET

moongloworklightusa.com